

PATENT APPLICATION

METHOD AND APPARATUS FOR UPGRADING MANAGED APPLICATION STATE FOR A JAVA BASED APPLICATION

INVENTORS: (1) Rahul Sharma
3267 Montelena Drive,
San Jose, CA 95135
Citizenship: India

(2) Vladimir Matena
1322 Kentfield Ave.
Redwood City, CA 94061
Citizenship: US

(3) Masood Mortazavi
1047 November Drive
Cupertino, CA 95014
Citizenship: US

(4) Sanjeev Krishnan
19932 Portal Plaza
Cupertino, CA 95014
Citizenship: India

ASSIGNEE: Sun Microsystems, Inc.
901 San Antonio Road, MS PAL01-521
Palo Alto, CA 94303

MARTINE PENILLA & KIM, LLP
710 Lakeway Drive, Suite 170
Sunnyvale, CA 94085
Telephone (408) 749-6900

METHOD AND APPARATUS FOR UPGRADING MANAGED APPLICATION STATE FOR A JAVA BASED APPLICATION

by Inventors

Rahul Sharma

Vladimir Matena

Max Mortazavi

Sanjeev Krishnan

CROSS REFERENCE TO RELATED APPLICATIONS

This application is related to (1) U.S. Patent Application No. _____ (Attorney Docket No. SUNMP002A), filed March 19, 2001, and "Method and Apparatus for Providing Application Specific Strategies to a Java Platform including Start and Stop Policies," (2) U.S. Patent Application No. _____ (Attorney Docket No. SUNMP002B), filed March 19, 2001, and entitled "Method and Apparatus for Providing Application Specific Strategies to a Java Platform including Load Balancing Policies," (3) U.S. Patent Application No. _____ (Attorney Docket No. SUNMP003), filed April 11, 2001, and entitled "Method and Apparatus for Performing Online Application Upgrades in A Java Platform," (4) U.S. Patent Application No. _____ (Attorney Docket No. SUNMP004), filed April 11, 2001, and entitled "Method and Apparatus for Performing Failure Recovery in a Java Platform," (5) U.S. Patent Application No. _____ (Attorney Docket No. SUNMP005), filed March 26, 2001, and entitled "Method and Apparatus for Managing Replicated and Migration Capable Session State for A Java Platform," (6) U.S. Patent Application No. _____ (Attorney Docket No. SUNMP006), filed April 2, 2001, and entitled "Method and Apparatus for Partitioning of Managed State for a Java based Application," and (7) U.S. Patent Application No. _____

_____ (Attorney Docket No. SUNMP008), filed April 30, 2001, and entitled “Method and Apparatus for Migration of Managed Application State for a Java based Application.” Each of the above related application are incorporated herein be reference.

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

This invention relates generally to Java programming, and more particularly to methods for performing online upgrades to the managed state of Java based applications.

2. Description of the Related Art

10 Today's world of computer programming offers many high-level programming languages. Java, for example, has achieved widespread use in a relatively short period of time and is largely attributed with the ubiquitous success of the Internet. The popularity of Java is due, at least in part, to its platform independence, object orientation and dynamic nature. In addition, Java removes many of the tedious and error-prone tasks that
15 must be performed by an application programmer, including memory management and cross-platform porting. In this manner, the Java programmer can better focus on design and functionality issues.

One particular Java environment is the Java 2 platform, Enterprise Edition (J2EE), which facilitates building Web-based and enterprise applications. Broadly speaking,
20 J2EE services are performed in the middle tier between the user's browser and the databases and legacy information systems. J2EE comprises a specification, reference implementation and a set of testing suites. J2EE further comprises Enterprise JavaBeans

(EJB), JavaServer Pages (JSP), Java servlets, and a plurality of interfaces for linking to information resources in the platform.

The J2EE specifications define how applications should be written for the J2EE environment. Thus the specifications provide the contract between the applications and the J2EE platform. One aspect of the J2EE specification is the EJB 2.0 Container Managed Persistence (CMP). The EJB 2.0 specification defines a contract between an entity bean, its container and the persistence manager for the management of persistent state and relationships for the entity beans. For a complete specification of CMP, refer to the EJB 2.0 specification published by Sun Microsystems, Inc., which is incorporated by reference herein in its entirety.

According to the EJB programming model, a bean provider develops a set of entity beans for an application and specifies the relationships between these objects. For each entity bean, the bean provider specifies an abstract persistence schema, which defines a set of methods for accessing the container-managed fields and relationships for the entity bean. The container-managed fields and relationships of the abstract persistence schema are specified in the deployment descriptor defined by the bean provider.

The deployer uses the persistence manager provider tools to determine how persistent fields and relationships are mapped to the underlying persistence mechanism, such as, a database. The persistence manager tools also generate the additional classes and interfaces that enable the persistence manager to manage the persistent fields and relationships of the entity beans at the runtime. An advantage of container managed persistence is that the entity beans become logically independent of the underlying

persistence mechanism. The CMP also leads to a simple programming mode for managing persistence.

5 An entity bean with container manager persistence includes its class, a remote or local interface that defines its client-view business methods, a home interface that defines create, remove, home and finder methods. The abstract persistence schema comprises a set of properties, each representing a field or relationship in the persistent state of entity bean. The entity bean defines a set of accessor (setter and getters) methods for the persistent fields and relationships.

10 The bean provider generally does not write any database access calls in the entity bean class. Instead, a persistence manager that is available to the container at runtime handles the persistence. The bean provider codes all persistent data access using the setter and getter methods defined for the container-managed persistent and relationship fields.

15 Figure 1 is a diagram showing the tradeoffs that business and carrier grade applications have to make. The carrier grade applications, which are applications used in high-performance, high-traffic networks such as used by telecoms, service providers and ISPs, require higher performance and availability than business applications.

20 Carrier grade (CG) applications require high availability of the order of five 9's and better. A high availability environment is one in which a service or component has greater availability, usually due to component redundancy, than in some base environment. Typically the term is used to describe failover cluster environment in which a service is provided by a primary component, until after some failure, after which the

secondary component takes over the provision of the service. The high availability requirement for carrier grade applications leads to a requirement for a carrier grade application to achieve prompt (two seconds or less) restart or failover to a secondary component with minimal disruption of service. Thus, the application has to become operational within minimal time after a failure.

A carrier grade application requires a shorter failover time as compared to the business applications, which typically store persistent state in a database to achieve ACID (Atomicity, Consistency, Isolation, Durability) properties for the managed state. Business applications rely on database-specific mechanisms to achieve state replication, thereby protecting persistent data from the failure of the primary database.

A typical database replication mechanism is database log replay. The database logs changes in a transaction log that is used for transaction replay in case of a failure. The log replay involves applying the transaction log to a replica database so that a near-mirror copy of primary database is created. Unfortunately, the time-delay in replaying the transaction log on the replica database slows down the failover. Moreover, a huge rate of inserts/updates may create huge transaction replay log, which further slows the transaction replay at the failure time.

Business applications also rely on parallel database servers to achieve state replication and failover. In case of parallel database servers, multiple active database engines, coordinated by a distributed lock manager, manage active replication. However, use of the distributed lock manager for coordinating database operations slows down the application performance. Hence, the use of a parallel database server is considered more suitable for read-only and read-mostly applications. With the short failover time

requirement, a typical carrier grade application cannot rely on a database-based replication mechanism or a parallel database server to achieve state replication and failover.

Business applications typically need to maintain ACID properties for the data being used by the application. Such applications cannot afford any data inconsistency and thereby store persistent data in a database and use transactions. For business applications, the tradeoff between consistency and concurrency gets reflected in the choice of the database isolation level. The use of optimistic concurrency model as against pessimistic concurrency model is another design decision involved in the business applications as part of the consistency and concurrency tradeoff. Business applications also need a reliable and consistent database failover and recovery—these applications cannot afford any inconsistent data.

The carrier grade applications may have consistency and concurrency requirements that differ from the business applications. A carrier grade application may process multiple concurrent state transitions and may not require full ACID properties to be maintained for its managed state. For example, a CG J2EE application may need a fast failover and may afford to have the replica (now the new primary) take over in a state that is temporally inconsistent with the initial primary. The client using the carrier grade application should be able to bring the new primary into a consistent state by retrying transactions for state transitions. Moreover, there currently is no defined mechanism for online upgrades of software on a J2EE platform. Such upgrades require the system to continue providing services to clients while the system software upgrade is being performed.

[illegible]

SUMMARY OF THE INVENTION

Broadly speaking, the present invention fills these needs by providing an upgrading mechanism that allows online upgrades of state schemas, including the managed state, both application specific and session related state, without disrupting the functionality of a running application during the upgrade process. In one embodiment, a method for upgrading schema for a managed state for a Java based application is disclosed. A Java module is executed on a server, where the Java module includes at least one original entity bean and at least one original state object in communication with the original entity bean. The original state object (part of the representation of managed state schema) stores a state of the original entity bean. Then, an upgraded state object is generated and the state stored in the original state object is transferred to the upgraded state object. In this manner, state management for the original entity bean can be provided using the upgraded state object. In addition, an upgraded entity bean is made operational and the state of the upgraded entity bean is managed using the upgraded state object. Thereafter, both the original entity bean and the original state object can be disabled. In this manner, the functionality of the Java module is not disrupted when the upgrade of state schema is performed. Also, the functionality of the Java application is not disrupted when the Java module is upgraded.

In another embodiment, a Java platform capable of performing an online upgrade on a Java application is disclosed. The Java platform includes a Java module having at least one original entity bean and at least one original state object in communication with the original entity bean. The original state object stores a state of the original entity bean, and provides state management for the original entity bean. The Java platform also

includes a repository having upgraded class files for the original entity bean and upgraded class files the original state object. The original state object is upgraded by generating an upgraded state object using upgraded class files from the repository, and transferring the state stored in the original state object to the upgraded state object. Further, the original
5 entity bean can be upgraded by creating an upgraded entity bean. Then, the state of the upgraded entity bean can be managed using the upgraded state object, and both the original entity bean and the original state object can be disabled.

A method for upgrading a Java application having a managed application state is disclosed in a further embodiment of the present invention. A Java module is executed
10 on a server, where the Java module includes at least one original entity bean and at least one original state object in communication with the original entity bean. As discussed above, the original state object stores a state of the original entity bean. Then, an upgraded state object is generated using data stored in a system repository, and the state stored in the original state object is transferred to the upgraded state object. State
15 management for the original entity bean is then provided using the upgraded state object. Next, an upgraded entity bean is created using data stored in the system repository, and state management for the upgraded entity bean is provided using the upgraded state object. Thereafter, both the original entity bean and the original state object are disabled.

Advantageously, the embodiments of the present invention allow online upgrades
20 to the managed state schema of a Java application. Further, the embodiments of the present invention allow upgrades to the application without disrupting the functionality of the application during the online upgrading process. As a result, applications executing on the Java system of the embodiments of the present invention can, in some

embodiments, achieve continuous availability, on the order of about 99.9999% uptime or better. Other aspects and advantages of the invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of the invention.

1000 999 998 997 996 995 994 993 992 991 990 989 988 987 986 985 984 983 982 981 980 979 978 977 976 975 974 973 972 971 970 969 968 967 966 965 964 963 962 961 960 959 958 957 956 955 954 953 952 951 950 949 948 947 946 945 944 943 942 941 940 939 938 937 936 935 934 933 932 931 930 929 928 927 926 925 924 923 922 921 920 919 918 917 916 915 914 913 912 911 910 909 908 907 906 905 904 903 902 901 900 899 898 897 896 895 894 893 892 891 890 889 888 887 886 885 884 883 882 881 880 879 878 877 876 875 874 873 872 871 870 869 868 867 866 865 864 863 862 861 860 859 858 857 856 855 854 853 852 851 850 849 848 847 846 845 844 843 842 841 840 839 838 837 836 835 834 833 832 831 830 829 828 827 826 825 824 823 822 821 820 819 818 817 816 815 814 813 812 811 810 809 808 807 806 805 804 803 802 801 800 799 798 797 796 795 794 793 792 791 790 789 788 787 786 785 784 783 782 781 780 779 778 777 776 775 774 773 772 771 770 769 768 767 766 765 764 763 762 761 760 759 758 757 756 755 754 753 752 751 750 749 748 747 746 745 744 743 742 741 740 739 738 737 736 735 734 733 732 731 730 729 728 727 726 725 724 723 722 721 720 719 718 717 716 715 714 713 712 711 710 709 708 707 706 705 704 703 702 701 700 699 698 697 696 695 694 693 692 691 690 689 688 687 686 685 684 683 682 681 680 679 678 677 676 675 674 673 672 671 670 669 668 667 666 665 664 663 662 661 660 659 658 657 656 655 654 653 652 651 650 649 648 647 646 645 644 643 642 641 640 639 638 637 636 635 634 633 632 631 630 629 628 627 626 625 624 623 622 621 620 619 618 617 616 615 614 613 612 611 610 609 608 607 606 605 604 603 602 601 600 599 598 597 596 595 594 593 592 591 590 589 588 587 586 585 584 583 582 581 580 579 578 577 576 575 574 573 572 571 570 569 568 567 566 565 564 563 562 561 560 559 558 557 556 555 554 553 552 551 550 549 548 547 546 545 544 543 542 541 540 539 538 537 536 535 534 533 532 531 530 529 528 527 526 525 524 523 522 521 520 519 518 517 516 515 514 513 512 511 510 509 508 507 506 505 504 503 502 501 500 499 498 497 496 495 494 493 492 491 490 489 488 487 486 485 484 483 482 481 480 479 478 477 476 475 474 473 472 471 470 469 468 467 466 465 464 463 462 461 460 459 458 457 456 455 454 453 452 451 450 449 448 447 446 445 444 443 442 441 440 439 438 437 436 435 434 433 432 431 430 429 428 427 426 425 424 423 422 421 420 419 418 417 416 415 414 413 412 411 410 409 408 407 406 405 404 403 402 401 400 399 398 397 396 395 394 393 392 391 390 389 388 387 386 385 384 383 382 381 380 379 378 377 376 375 374 373 372 371 370 369 368 367 366 365 364 363 362 361 360 359 358 357 356 355 354 353 352 351 350 349 348 347 346 345 344 343 342 341 340 339 338 337 336 335 334 333 332 331 330 329 328 327 326 325 324 323 322 321 320 319 318 317 316 315 314 313 312 311 310 309 308 307 306 305 304 303 302 301 300 299 298 297 296 295 294 293 292 291 290 289 288 287 286 285 284 283 282 281 280 279 278 277 276 275 274 273 272 271 270 269 268 267 266 265 264 263 262 261 260 259 258 257 256 255 254 253 252 251 250 249 248 247 246 245 244 243 242 241 240 239 238 237 236 235 234 233 232 231 230 229 228 227 226 225 224 223 222 221 220 219 218 217 216 215 214 213 212 211 210 209 208 207 206 205 204 203 202 201 200 199 198 197 196 195 194 193 192 191 190 189 188 187 186 185 184 183 182 181 180 179 178 177 176 175 174 173 172 171 170 169 168 167 166 165 164 163 162 161 160 159 158 157 156 155 154 153 152 151 150 149 148 147 146 145 144 143 142 141 140 139 138 137 136 135 134 133 132 131 130 129 128 127 126 125 124 123 122 121 120 119 118 117 116 115 114 113 112 111 110 109 108 107 106 105 104 103 102 101 100 99 98 97 96 95 94 93 92 91 90 89 88 87 86 85 84 83 82 81 80 79 78 77 76 75 74 73 72 71 70 69 68 67 66 65 64 63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33 32 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

BRIEF DESCRIPTION OF THE DRAWINGS

The invention, together with further advantages thereof, may best be understood by reference to the following description taken in conjunction with the accompanying drawings in which:

5 Figure 1 is a diagram showing the tradeoffs that business and carrier grade applications have to make;

Figure 2 is a Java system having state management, in accordance with an embodiment of the present invention;

10 Figure 3 is a block diagram showing replicated state subsystems, in accordance with an embodiment of the present invention;

Figure 4 is a diagram showing state management types for state management units (SMU), in accordance with an embodiment of the present invention;

Figure 5 is an illustration showing a hierarchy of use operations for an RSM, in accordance with an embodiment of the present invention;

15 Figure 6 is a class diagram showing repository interfaces used by the RSM, in accordance with an embodiment of the present invention;

Figure 7 is a sequence diagram showing an application upgrade sequence, in accordance with an embodiment of the present invention;

20 Figure 8 is a diagram showing upgrade operations for upgrading the managed state of an application, in accordance with an embodiment of the present invention; and

Figure 9 is a sequence diagram showing an upgrade managed state sequence, in accordance with an embodiment of the present invention.

Figure 9 is a sequence diagram showing an upgrade managed state sequence, in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

An invention is disclosed for systems and methods that provide online upgrading of the schema of managed state for Java based applications, including applications requiring high availability. To this end, embodiments of the present invention provide a subsystem that manages the replicated and migration capable state for an Enterprise Java Bean (EJB) application. This subsystem is further capable of upgrading the managed state schema of an application using state objects, while the application continues to process requests. In the following description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be apparent, however, to one skilled in the art that the present invention may be practiced without some or all of these specific details. In other instances, well known process steps have not been described in detail in order not to unnecessarily obscure the present invention.

Figure 1 has been described in terms of the prior art. Figure 2 is a Java system 200 having state management, in accordance with an embodiment of the present invention. The Java system 200 includes an application runtime subsystem 202 having a Java 2 Enterprise Edition (J2EE) Server 204 and a replicated state manager (RSM) subsystem 206. Also included in the Java system 200 are a Java application 208, a repository subsystem 210, a disk replicated state server subsystem 212, and a memory replicated state server subsystem 214.

Figure 2 shows the RSM 206 interfacing with the (J2EE) Server 204, the Java application 208, the repository 210, the disk replicated state server subsystem 212, and the memory replicated state server subsystem 214. The J2EE Server subsystem 204

provides the runtime environment for J2EE applications, and includes implementations of different types of J2EE containers, such as an application client container, an EJB container, and a web container.

5 The Repository subsystem 210 stores and manages the software load for the J2EE application 208 and J2EE server 204. During pre-deployment of a J2EE application 208, classes and a deployment descriptor provided by an application developer are loaded into the repository 210, and later, loaded on to a J2EE server 204 to make the application 208 operational.

10 State server subsystems store and manage the replicated state for the J2EE application 208, which makes an application highly available. During application runtime, the RSM 206 replicates the replicated state to a state server. If the application 208 running on the J2EE server 204 fails, the application 208 restarts after failure by recovering its state from the replicated state server. The Java system 200 provides two types of state servers, a memory replicated state server 214 and a disk replicated state server 212. The memory replicated state server 214 stores the replicated state in an in-memory database, while disk replicated state server 212 uses a disk-based database to store and manage the replicated state.

20 As shown in Figure 2, the RSM subsystem 206 is part of the J2EE Application Runtime subsystem 202, which is responsible for management and supervision of running the J2EE application 208. The RSM 206 manages the replicated and migration capable state for J2EE applications 208 that are running on a J2EE server 204. By managing application state, the RSM 204 provides support for online application upgrades, failure recovery and load balancing features of the J2EE system 200. The RSM 206 uses a

memory database within a J2EE server process 204 to manage the application state. In this manner, the RSM enables an application to remain operational even if the state servers become temporary unavailable.

Figure 3 is a block diagram showing replicated state subsystems 300, in accordance with an embodiment of the present invention. The replicated state subsystems 300 show a J2EE server 204 in communication with a disk replicated state server 212, and a memory replicated state server 214. Based on the CMP model, the application developer develops a set of entity beans 304 for an application and specifies the relationships between these objects. For each entity bean 304, the application developer specifies an abstract schema that defines a set of methods for accessing the container-managed fields and relationships for the entity bean. These container-managed fields and relationships are specified in the deployment descriptor defined by the application developer.

Each entity bean 304 includes an abstract class, a local and/or remote interface that defines bean's client-view business methods, a home interface that defines create, remove, home and finder methods. The abstract schema includes a set of properties, with each property representing a field or relationship in the container-managed state of the entity bean 304. The entity bean 304 also defines a set of setter and getters methods for the container-managed fields and relationships. The application developer codes state access and modifications using the setter and getter methods defined for the container-managed fields and relationships.

The EJB 2.0 CMP specification sets forth, without specific implementations, goals for a persistence manager that provides management of persistent state and

relationships for the entity beans 304. The embodiments of the present invention provide specific methods for state management that achieve the goals set forth by the EJB 2.0 CMP specification. Specifically, the RSM of the embodiments of the present invention is a carrier-grade J2EE specific implementation of a persistence manager facility.

5 However, instead of mapping an abstract schema to a database-based persistence mechanism, RSM manages the state of entity beans 304 and dependent objects 306 using an in-memory state management facility. This in-memory state manager runs within a J2EE server process. To support state recovery during an application restart and migration, the RSM actively replicates the in-memory state to disk replicated state servers
10 212 and/or memory replicated state servers 214.

Figure 3 shows two EJB modules 302 deployed on a J2EE server process 204. Each EJB module 302 includes a set of entity beans 304. The RSM defines a separation between the application part 350 and managed state part 352.

The application part 350 includes abstract entity bean object classes 304 provided
15 by application developer, based on the EJB 2.0 CMP model. The application part 350 also includes concrete implementation classes generated by the RSM. Further, the application part 350 provides the implementation of methods that provide the state transition logic for a J2EE application.

The Managed state part 352 includes the state objects 314 that capture the state of
20 entity beans 304. The separation of state between application part 350 and managed state part 352 enables the RSM to support both application upgrade and migration.

The RSM of the embodiments of the present invention can generate concrete implementation classes for entity beans 304. The concrete classes generated by the RSM are responsible for managing the recoverable state of the entity beans 304. The RSM also provides implementation of collection classes that are used in managing container-
5 managed relationships. By providing implementation of the getter and setter methods of the corresponding abstract classes, the RSM can implement the entity bean 304 classes. The RSM can also manage the mapping between primary keys and EJB objects, and can store the recoverable references to the remote and home interfaces of other EJBs.

The RSM further manages the relationships between entity beans 304. This
10 includes maintaining the referential integrity of the container-managed relationships in accordance with the semantics of the relationship type.

The RSM manages the recoverable state of entity bean 304 based on the type of the state. Depending on the type of state, the RSM replicates the state in either a disk replicated state server 212 or a memory replicated state server 214. In addition, the RSM
15 makes application state capable of migration from one J2EE server process 204 to another J2EE server process.

The RSM supports checkpoints of the recoverable state to the two types of state servers, namely, the disk replicated state server 212 and the memory replicated state server 214. This includes support for connecting to the servers, sending checkpoints,
20 recovering replicated state and merging the recovered state into existing in-memory state. Further, the RSM recovers the replicated state from the state servers during application restart after a failure or shutdown or during migration of EJB module from one J2EE server process to another.

During pre-deployment of an EJB module 302, the RSM maps the abstract schema of entity beans 304 classes to a physical schema used by the RSM. To perform this form of schema mapping, the RSM can use a deployment descriptor of EJB components. The RSM generates concrete implementations for the entity bean 304 classes defined as abstract classes by the application developer. A concrete implementation class includes the code that implements the setter and getter methods for container-managed fields and relationships based on the RSM mechanism.

The embodiments of the present application allow state managed by the RSM for a J2EE application to be partitioned into multiple state partitions. In some embodiments of the present invention a state partition defines a unit of concurrency. In these embodiments, the RSM serializes access to a state partition from concurrent transactions. For example, using this embodiment, if a J2EE application includes multiple entity beans having states managed as part of a single state partition, then only a single transaction can be active across the entity bean instances in this state partition at any particular instance.

During application design, application designer partitions the replicated and migration capable state of an application using State Management Units of different types and State Partition. Such state partitioning may be specified using an application configuration descriptor or done dynamically through control module. The repository maintains a representation for the static partitioning of state using schema archives. Schema archives are described in greater detail in U.S. Patent Application No. _____ (Attorney Docket No. SUNMP005), filed March 26, 2001, and entitled "Method and Apparatus for Managing Replicated and Migration Capable Session State for A Java Platform," which is incorporated herein by reference in its entirety.

RSM partitions entity beans based on the range of primary keys that will be served by different state partitions. For example, account 1 to 100 will be managed within a single state partition 1, while account 101 to 200 will be managed in a separate state partition 2. A state partition also identifies the unit of concurrency. J2EE server process and RSM serialize transactional access to a state partition. At any specific instance, there can be only one transaction active on entity beans within a state partition.

After partitioning state into State Partitions, application designer partitions each state partition into multiple State Management Units. A state partition can contain multiple state management units (SMU) of different types.

Figure 4 is a diagram showing state management types 400 for state management units (SMU), in accordance with an embodiment of the present invention. The state management types 400 are divided into a non-recoverable state 402 and recoverable states 404. The non-recoverable state 402 includes a non-replicated state 406. The recoverable states include a disk replicated state 408 and a memory replicated state 410.

A SMU is a collection of state objects 314 with the same state management type 400, and further defines a unit of checkpoints for the recoverable state types 404. An application can include multiple SMUs of different types depending on the specific requirements of the application. The RSM replicates a disk replicated SMU 408 to a disk replicated state server. The RSM is then capable of automatically recovering the disk replicated SMU 408 during an application restart after failure, shutdown or migration.

The RSM replicates a memory replicated SMU 410 to a memory replicated state server, and is then capable of automatically recovering memory replicated SMU 410

during an application restart after failure, shutdown or migration. The not replicated SMU 406 is not replicated by the RSM to either a disk replicated state server or a memory replicated state server. Generally, the RSM manages a non-replicated SMU 406 to support the migration state of a J2EE application from one J2EE server process to another.

Figure 5 is an illustration showing a hierarchy of use cases 500 for an RSM, in accordance with an embodiment of the present invention. During application runtime, a Control Module 550, an EJB Container 552, a Transaction Manager 556, and an EJB Client 554 are the actors that drive use cases for the RSM.

The control module 550 is a part of a Java application that provides control and application-specific policies for the application. The control module 550 is described in greater detail in related U.S. Patent Application No. _____ (Attorney Docket No. SUNMP002A), filed March 19, 2001, and entitled "Method and Apparatus for Providing Application Specific Strategies to a Java Platform including Start and Stop Policies," which is incorporated by reference in its entirety. The control module 550 is responsible for supervising the J2EE server 204 and the EJB modules at application runtime. Since the RSM is part of application runtime for a J2EE server process 204, J2EE server 204 activates the RSM as part of the start J2EE server process 502, the upgrade module process 504, and the move module process 506. The control module 550 interacts with the J2EE server 204, which in turn drives uses cases for RSM.

The EJB client 554 invokes a method on an entity bean that has its state managed by the RSM using a manage application state process 510. Such method invocation generally happens under a transaction, and drives the RSM to manage any changes to the

entity bean's state as part of the invocation. The EJB container 552, which is part of J2EE server 204, intercepts the method invocation to inject its services, for example, the container 552 can start a transaction that brackets a method invocation. After injecting its services, the container 552 dispatches method invocation to the target entity bean instance. The EJB container 552 interfaces with the RSM to drive the manage transactions use case 512, the manage application state use case 510, and the manage checkpoints use case 514. Finally, the transaction Manager 556 manages transactions for the RSM, which acts as a transactional resource manager.

The RSM uses the manage application state use case 510 to manage state for an EJB-based application. The RSM acts as a carrier-grade implementation of the persistence manager facility defined in the EJB 2.0 specification. CMP model uses the RSM to manage replicated and migration-capable state for entity bean.

Initially, the EJB client 554 makes an invocation on a method defined as part of the remote or local interface of the target entity bean. Typically, a method invocation maps to a state transition implemented by the entity bean. Based on the CG J2EE programming model, a method invocation on an entity bean can be either local or distributed, synchronous or asynchronous, but preferably does not have any affect on how the RSM manages state for an invoked entity bean instance.

The EJB container 552 then intercepts the method invocation from the EJB client. The EJB container 552 uses this interception to inject container-specific services, such as, transaction bracketing and security mapping. As part of the method implementation, abstract entity bean classes provided by the application developer invoke setter and getter methods for container-managed fields and relationships. A concrete implementation

class is then generated by the RSM and implements the setter and getter methods. This enables the RSM to manage the state of container-managed fields and relationships as part of its implementation. The RSM manages the state of entity beans using an in-memory state management facility, which runs within a J2EE server process.

5 When an entity bean undergoes state transitions initiated by a client application, the application changes the state objects. Any changes to the managed state part are tracked by the RSM. Depending on the state management requirements specified for a J2EE application, the RSM replicates the state objects to disk replicated and memory replicated state servers.

10 The RSM uses the manage checkpoint process 514 to manage checkpoints of replicated state, and then issues checkpoints to the state servers. More specifically, the RSM implements a checkpoint mechanism that is configurable using a checkpoint policy, which can be specified by the application Control Module 550. The RSM then uses the checkpoint mechanism to replicate state to the disk replicated state server and the
15 memory replicated state server.

 The RSM can issue checkpoints at different points, such as at the successful commit of each transaction. Generally, no checkpoint is issued for a transaction that fails to commit and is rolled back. This ensures that the state is replicated to state servers for only committed transactions leading to consistent recovery after failure, migration or
20 shutdown. The RSM can optimize the checkpoint mechanism by combining transactions from successful commits of multiple transactions, and maintaining a sequence of box-carried checkpoints. This is referred to as boxcarring of checkpoints for multiple transactions.

Further, the checkpoint can be issued either synchronously or asynchronously. The synchronous checkpointing increases the reliability associated with the checkpointing mechanism. The state server ensures that checkpoints propagated to it are processed, thereby avoiding any potential loss of checkpoints. The replicated state in the state servers
5 stays identical with the in memory state managed by RSM, ensuring a faster recovery during the failover.

In the asynchronous checkpoint mechanism, the RSM on the J2EE server process can enqueue checkpoints on a local message queue, thus the checkpoint messages are placed in the local address space before getting dispatched. The checkpoint operation
10 returns immediately after the enqueueing operation allowing the on-going transaction to complete.

The message queue takes the responsibility of delivering the checkpoint messages to the state server at some time later after the transaction has been successfully committed. Preferably, the message queue preserves the ordering of the checkpoint
15 messages in the order that transactions were executed on the application.

Asynchronous checkpointing adds more flexibility to the state replication mechanism. Based on the checkpointing policy, the message queue can take decision to propagate asynchronous checkpoints at different intervals—after each committed transaction, after a set of committed transactions or after a defined time interval.

20 Figure 6 is a class diagram showing repository interfaces 600 used by the RSM, in accordance with an embodiment of the present invention. The repository maintains classes and configuration descriptors that represent partitioning of state for a J2EE

application. The repository interfaces 600 includes EJB modules 302, a logical schema archives 602, a physical schema archives 604, entity bean classes 606, SMU archives 610, and state object classes 612.

The RSM maintains both a logical schema archive 602 and a physical schema
5 archive 604 for each EJB module 302, which are populated in the repository 210 during pre-deployment of an EJB module 302. More specifically, during pre-deployment of the EJB module 302, the RSM creates a logical schema archive 602 in the repository, which includes abstract classes for entity beans 606. The logical schema archive 602 also includes concrete implementation classes that are generated by the RSM. The RSM maps
10 the logical schema archive of a pre-deployed J2EE application to the application part at runtime.

The physical schema archive 604 includes the state object classes 612 and RSM-generated artifacts used for the managed state part of a J2EE application. The SMU archive 610 groups state object classes 612 based on the state management type. Multiple
15 SMU archives 610 can be included within a physical schema archive 604. Both logical and physical schema archives are loaded in the repository as part of application software load.

As previously mentioned, the embodiments of the present invention can perform online upgrades to schema for both session and application-specific managed state , while
20 the application continues to process new requests. Specifically, the embodiments of the present invention can be used in service-provider environments that require a mechanism to perform online upgrades of an application. Using the embodiments of the present invention, a system can continue to provide services to clients while a software upgrade is

being performed. Advantageously, the embodiments of the present invention allow an online upgrade to occur generally without any detectable impact on the clients using the services provided by the application during the upgrade.

Figure 7 is a sequence diagram showing an application upgrade sequence 700, in accordance with an embodiment of the present invention. The application upgrade sequence 700 illustrates how a parent application's control module 550 upgrades a child application. Broadly speaking, the child application's control module is upgraded in-place. Then, the child application's control module upgrades the application's J2EE servers, service modules, and child applications.

More specifically, in operation 701, the parent application's control module 550 requests the executive 202 to upgrade a child application. Advantageously, the request can include optional application-specific data that the executive 202 will pass to the target application's control module. Next, in operation 702, the executive 202 requests the J2EE Server 204 running the application's old control module 750a to upgrade the old control module 750a.

In response, the J2EE Server 204 begins the upgrade by loading the class files for the upgraded physical RSM schema of the control module from the repository 210, in operation 703. The J2EE Server 204, in operation 704, then performs an online upgrade of the control module's state to the new physical schema. The J2EE Server 204 also upgrades the control module's state server partitions in the state server 212/214 to the new state schema, in operation 705.

The J2EE Server 204 then creates a new instance 750b of the old control module 750a, in operation 706, and loads the new class files for the new control module 750b, in operation 707. After loading the new class files, the J2EE Server 204, in operation 708, disables requests to the old control module 750a, and enables requests to new control module 750b. In this manner, requests from other application modules or from external applications can now be directed to the new control module 750b. The J2EE Server 204 then deletes the old control module 750a, in operation 710, and reports completion to the executive 202, in operation 711.

In operation 712, the executive 202 requests the new control module 750b to continue the upgrade. In response, the new control module 750b upgrades all child J2EE Servers, in operation 713. The new control module 750b also upgrades all application service modules, in operation 714, and upgrades all child applications by recursively using the application upgrade sequence 700, in operation 714.

When all the application's service modules, child J2EE servers, and child applications have been upgraded, the new control module 750b reports completion to the executive 202, in operation 716. The completion message may include optional application-specific data to be passed to the parent application's control module 550. Then, in operation 717, the executive 202 reports completion to parent applications control module 550, passing the application-specific data from the new control module 750b.

Figure 8 is a diagram showing upgrade operations 800 for upgrading the managed state of an application, in accordance with an embodiment of the present invention. The upgrade operations 800 illustrate how the RSM upgrades the state of an EJB module as

part of module upgrade. As discussed above, the application control module supervises the upgrade of an EJB module by interacting with the J2EE server, which in turn drives the use cases for the RSM.

In operation 802, an EJB module having an application part 350 and a managed state part 352 is executed. The application part 350 includes a plurality of entity beans, of which entity bean 304a is a member. Similarly, the managed state part 352 of the EJB module includes a plurality of state objects, of which state object 314a is a member. As illustrated, state object 314a maintains the managed state of the entity bean 304a. To upgrade the EJB module, the RSM begins by upgrading the managed state of the EJB module, as discussed next in operation 804.

In operation 804, the RSM performs an online upgrade of the managed state part 352 for the EJB module. This includes upgrading of existing physical schema to the upgraded physical schema archive. RSM uses the repository to load the upgraded physical schema archive. The RSM also upgrades the state contained in the SMUs. The RSM takes responsibility of transferring the state from existing state objects 314a to upgraded state objects 314b without disrupting module operation. In particular, after creating an upgraded state object 314b, the RSM uses the new upgraded state object 314b to maintain state for the entity bean 304a.

The J2EE server then takes the responsibility of upgrading the application part 350 of the EJB module, in operation 806. During the upgrade of the application part 350, the existing EJB module continues to process method invocations using the upgraded managed state objects 314b. As discussed above with reference to Figure 7, the J2EE Server creates an upgraded entity bean 304b for each old entity bean 304a. Then, the

J2EE server disables the existing entity bean 304a and enables the upgraded entity bean 304b. During this switchover, J2EE server waits for pending requests on running EJB module to drain before switching. Thus EJB module is upgraded with minimal downtime.

5 Figure 9 is a sequence diagram showing an upgrade managed state sequence 900, in accordance with an embodiment of the present invention. The upgrade managed state sequence 900 illustrates how the RSM upgrades the managed state for an EJB module. In operation 901, the applications control module 550 requests the J2EE server 204 to upgrade an existing EJB module 302a. In response, the J2EE server 204 initiates upgrade
10 of the managed state part for the existing EJB module 302a by requesting the RSM 206 to upgrade the managed state part of the EJB module, in operation 902.

 In operations 903 and 904, the RSM 206 loads the upgraded Physical Schema Archive for the EJB module from the repository 210, and in operation 905, the RSM 206 loads the Physical Schema classes from the class loader 950. In operations 906, 907, and
15 908, the RSM 206 creates the upgraded State Partitions and SMUs based on the physical schema specification. In addition, the RSM 206 initiates upgrade of created SMUs and state objects contained within the SMUs.

 Next, in operations 909, 910, 911, and 912, the RSM 206 creates an instance of an upgraded state object class, such as a new version of OrderState class with an upgraded
20 set of fields as defined by a compatible upgrade. The RSM 206 then transfers the state from instances of the existing state object class to those of upgraded state object class. It should be noted that transfer of the state accounts for any changes in the schema of two state object class.

Once the state transfer is completed for an upgraded SMU from an existing SMU, the RSM 206 discards the old SMU and its state objects. The, RSM 206 then begins using the upgraded SMU to manage state. After the state upgrade is completed for a SMU, the RSM 206 upgrades the schema in the state servers for the upgraded SMU and state object classes, in operations 913 and 914. In this manner, the RSM 206 upgrades all the SMUs for the EJB module.

After completing the state upgrade, the J2EE server 204 takes the responsibility of upgrading application part of the EJB module 302a, in operation 915. This includes the operations of loading new logical schema for upgraded EJB module, in operation 916, disabling existing EJB module 302a, in operation 918, and enabling the upgraded EJB module 304b, in operation 919. Advantageously, the embodiments of the present invention allow online upgrades to the managed state of a Java application. Further, the embodiments of the present invention allow upgrades to the application without disrupting the functionality of the application during the online upgrading process.

Although the foregoing invention has been described in some detail for purposes of clarity of understanding, it will be apparent that certain changes and modifications may be practiced within the scope of the appended claims. Accordingly, the present embodiments are to be considered as illustrative and not restrictive, and the invention is not to be limited to the details given herein, but may be modified within the scope and equivalents of the appended claims.

What is claimed is: